


## GS1920-24HPv2

<b>Model</b>	
Product name	24-port GbE Smart Managed PoE Switch
Switch class	Smart Managed
<b>Port Density</b>	
Total port count	28
100/1000 Mbps	24
Gigabit Combo (RJ-45/SFP)	4
Gigabit SFP	-
<b>PoE</b>	
PoE ports	24
Total PoE budget (Watts)	375
High power PoE 802.3at	Yes
<b>Performance</b>	
Switching capacity (Gbps)	56
Forwarding rate (Mpps)	42
Packet buffer (byte)	1.5 M
MAC address table	16 K
Flash/RAM	32 MB/256 MB
<b>Power</b>	
Input	100 to 240 V AC, 50/60 Hz
Max. power consumption (watt)	463.5
<b>Physical Specifications</b>	
Item	<b>Dimensions (WxDxH)(mm/in.)</b> 441 x 270 x 44/ 17.36 x 10.63 x 1.73 <b>Weight (kg/lb.)</b> 3.8/8.38
Included accessories	Power cord Rack mounting kit
<b>Green Feature</b>	
Fanless	-
<b>Environmental Specifications</b>	
Operating	Temperature 0°C to 50°C/32°F to 122°F Humidity 10% to 90% (non-condensing)
Storage	Temperature -40°C to 70°C/-40°F to 158°F Humidity 10% to 90% (non-condensing)
MTBF (hr)	638,691
Heat dissipation (BTU/hr)	1,580.54
Acoustic noise @ 25°C (dBA)	27.2