


GS1920-24v2

Model	
Product name	24-port GbE Smart Managed Switch
Switch class	Smart Managed
Port Density	
Total port count	28
100/1000 Mbps	24
Gigabit Combo (RJ-45/SFP)	4
Gigabit SFP	-
PoE	
PoE ports	-
Total PoE budget (Watts)	-
High power PoE 802.3at	-
Performance	
Switching capacity (Gbps)	56
Forwarding rate (Mpps)	42
Packet buffer (byte)	1.5 M
MAC address table	16 K
Flash/RAM	32 MB/256 MB
Power	
Input	100 to 240 V AC, 50/60 Hz
Max. power consumption (watt)	22.5
Physical Specifications	
Item	Dimensions (WxDxH)(mm/in.) 441 x 131 x 44/ 17.36 x 5.16 x 1.73 Weight (kg/lb.) 2.1/4.63
Included accessories	Power cord Rack mounting kit
Green Feature	
Fanless	Yes
Environmental Specifications	
Operating	Temperature 0°C to 50°C/32°F to 122°F Humidity 10% to 90% (non-condensing)
Storage	Temperature -40°C to 70°C/-40°F to 158°F Humidity 10% to 90% (non-condensing)
MTBF (hr)	911,301
Heat dissipation (BTU/hr)	76.73
Acoustic noise @ 25°C (dBA)	0